NSN 5930-01-050-4352

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-050-4352

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Weatherproof
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.812 inches
Body Length:
2.000 inches
Body Width:
1.000 inches
Body Height:
1.125 inches
Case Material:
Metal
Unthreaded Mounting Hole Diameter:
0.171 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.468 inches
Actuator Length:
1.380 inches
Actuator Style:
Roller arm
Actuator Free Position Height:
2.590 inches
Actuator Roller Diameter:
0.500 inches
Actuator Roller Width:
0.125 inches
Maximum Voltage Rating In Volts:
28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
32.0 ounces
Switch Actuating Force:

128.0 ounces

NSN 5930-01-050-4352

Sensitive Switch - Page 2 of 2



Actuator Movement:

Between 0.145 pretravel inches and 0.219 overtravel inches and 0.065 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 6.000 amperes inductive dc

Terminal Type And Quantity:

1 connector, receptacle

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0