

View Online at <https://aerobasegroup.com/nsn/5930-01-050-5423>

**Body Style:**

Hole mounted

**Overall Length:**

0.875 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.500 inches

**Overall Height:**

1.303 inches

**Overall Width:**

0.420 inches

**Body Length:**

0.845 inches

**Body Width:**

0.250 inches

**Body Height:**

1.188 inches

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

0.088 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

0.373 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.120 inches

**Actuator Height:**

0.100 inches

**Actuator Free Position Height:**

0.396 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

3 two circuit, both positions maintained single switch unit

**Switch Release Force:**

4.0 ounces

**Switch Actuating Force:**

16.0 ounces

**Actuator Movement:**

Between 0.050 pretravel inches and 0.012 overtravel inches and 0.020 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes lamp dc and 7.500 amperes resistive ac and 5.000 amperes inductive ac and 3.000 amperes lamp ac

**Special Features:**

Two mtg holes and two mtg slots

**Precious Material And Location:**

Contacts silver and contact surfaces gold

**Terminal Type And Quantity:**

12 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0