

View Online at <https://aerobasegroup.com/nsn/5930-01-050-5423>

Body Style:

Hole mounted

Overall Length:

0.875 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.500 inches

Overall Height:

1.303 inches

Overall Width:

0.420 inches

Body Length:

0.845 inches

Body Width:

0.250 inches

Body Height:

1.188 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.088 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.373 inches

Actuator Style:

Round

Actuator Diameter:

0.120 inches

Actuator Height:

0.100 inches

Actuator Free Position Height:

0.396 inches

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

3 two circuit, both positions maintained single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

16.0 ounces

Actuator Movement:

Between 0.050 pretravel inches and 0.012 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes lamp dc and 7.500 amperes resistive ac and 5.000 amperes inductive ac and 3.000 amperes lamp ac

Special Features:

Two mtg holes and two mtg slots

Precious Material And Location:

Contacts silver and contact surfaces gold

Terminal Type And Quantity:

12 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0