NSN 5930-01-050-5724

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-050-5724

Thread Class:

2a single mounting facility

Thread Length:

0.437 inches single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

1.822 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.216 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.437 inches single actuator

Overall Diameter:

1.190 inches

Individual Section Quantity:

Nonturn Device Type:

Slotted bushing at 4: 30 o'clock

Operating Tempurature Range:

-65.0/+125.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section front

Throw Quantity:

20 single section rear

Mounting Method:

Threaded bushing w/panel seal single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

198.0 degrees from nonturn device single actuator

Rotor Through Connection Quantity:

1 single section

Switch Actuator Indexing Position Quantity:

20 single actuator

NSN 5930-01-050-5724

Rotary Switch - Page 2 of 2

A052b0



Shaft Type:
Round, flatted single actuator
Terminal Type:
Tab, solder lug
Contact Switching Action:
Breaks before makes single section rear
Switch Actuator Positioning Increment:
18.0 degrees single actuator
Detent Rotational Torque Range:
+0.500/+2.500 inch-pounds single actuator
Contact Load Current Rating:
25.0 milliamperes resistive load ac at sea level
Style Designator:
Tap, circular, bushing mount
Test Data Document:
81349-mil-s-3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef single mounting facility
Specification Data:
81349-mil-s-3786/36 government specification
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig: