

View Online at <https://aerobasegroup.com/nsn/5930-01-050-6627>

Hazardous Locations/environmental Protection:

Dustproof

Overall Height:

1.080 inches

Overall Width:

2.450 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.217 inches single actuator and 0.219 inches single actuator

Shaft Diameter:

0.249 inches single actuator and 0.251 inches single actuator

Unthreaded Mounting Hole Diameter:

0.041 inches single mounting facility

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

1.240 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

0.660 inches single mounting facility

Switch Contact Basic Design:

Pile-up

Mounting Method:

Bracket single mounting facility and unthreaded hole single mounting facility

Features Provided:

Cam actuated

Contact Voltage Rating In Volts:

230.0 highest ac voltage rating at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section in-line

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Detent Rotational Torque Range:

+15.000/+40.000 inch-ounces single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

15.0 amperes resistive load lowest ac voltage rating at sea level

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0