

View Online at <https://aerobasegroup.com/nsn/5930-01-050-6627>

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Height:**

1.080 inches

**Overall Width:**

2.450 inches

**First Flat Length:**

0.250 inches single actuator

**Flat Height:**

0.217 inches single actuator and 0.219 inches single actuator

**Shaft Diameter:**

0.249 inches single actuator and 0.251 inches single actuator

**Unthreaded Mounting Hole Diameter:**

0.041 inches single mounting facility

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

1.240 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

0.660 inches single mounting facility

**Switch Contact Basic Design:**

Pile-up

**Mounting Method:**

Bracket single mounting facility and unthreaded hole single mounting facility

**Features Provided:**

Cam actuated

**Contact Voltage Rating In Volts:**

230.0 highest ac voltage rating at sea level

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

3 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes single section in-line

**Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Detent Rotational Torque Range:**

+15.000/+40.000 inch-ounces single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

15.0 amperes resistive load lowest ac voltage rating at sea level

**Style Designator:**

Tap, circuit selector

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0