

View Online at <https://aerobasegroup.com/nsn/5930-01-050-6629>

Overall Length:

3.370 inches

Outside Diameter:

0.213 inches single connection and 0.219 inches single connection

Overall Height:

4.175 inches

Body Diameter:

3.120 inches

Unthreaded Mounting Hole Diameter:

0.120 inches

Longest Horizontal Distance Between Mounting Centers:

0.500 inches

Longest Vertical Distance Between Mounting Centers:

1.240 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

10.0 amperes resistive load first voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

4.75 actuation point inches of water and 2.35 deactuation point inches of water and 2.40 differential point inches of water

Contact Voltage Rating In Volts:

250.0 ac at sea level first voltage

Pressure Connector Type:

Shoulder, unthreaded external single connection

Special Features:

Six mtg holes

Media For Which Designed:

Gas or liquid

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0