## NSN 5930-01-050-6637

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-050-6637

## Thread Length:

0.437 inches single mounting facility

## Hazardous Locations/environmental Protection:

Explosion proof

## **Overall Length:**

2.359 inches

#### First Flat Length:

0.250 inches single actuator

#### Shaft Diameter:

0.250 inches single actuator

## Shaft Length:

0.874 inches single actuator

## **Overall Diameter:**

1.170 inches

#### **Nonturn Device Radius:**

## 0.375 inches at 3: 00 o'clock

## Individual Section Quantity:

1

## Nonturn Device Type:

Tab at 3: 00 o'clock

## Switch Contact Basic Design:

Nonpile-up symmetrical

## Pole Quantity:

1 single section front

## **Throw Quantity:**

5 single section rear

## **Mounting Method:**

Threaded bushing single mounting facility

## Thread Size:

0.375 inches single mounting facility

## **Rotor Through Connection Quantity:**

1 single section

## Switch Actuator Indexing Position Quantity:

5 single actuator

## Shaft Type:

Round, flatted single actuator

## **Terminal Type:**

Tab, solder lug

## **Contact Switching Action:**

Breaks before makes single section rear

## Switch Actuator Positioning Increment:

30.0 degrees single actuator

# NSN 5930-01-050-6637

Rotary Switch - Page 2 of 2



Switch Actuator Stop Device Type:

Fixed stop single actuator

Style Designator:

Tap, circular, bushing mount

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A052b0