NSN 5930-01-050-6664

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-050-6664

view Offilite at https://aerobasegroup.com/hisri/0000-000-
Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Explosion proof and humidity resistant
Overall Length:
3.198 inches
Overall Height:
0.880 inches
Overall Width:
0.880 inches
Body Width:
0.850 inches
Body Height:
0.850 inches
Actuator Length:
0.530 inches
Actuator Style:
Rectangular
Actuator Height:
0.155 inches
Actuator Width:
0.530 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
Green single actuator
Actuator Inscription:
Fit single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Mounting Surface To Terminal End Distance:
2.747 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Full display lens and actuator seal and rfi shielding
Nonpile-up Contact Arrangement:
3 pole, single throw, normally closed, momentary action single switch unit
Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 7.500 amperes resistive ac and 5.000 amperes inductive ac and 1.000 amperes lamp ac

NSN 5930-01-050-6664

Push Switch - Page 2 of 2



Tarminal	T	A (Quantity:
remma	I VDE	Allu v	zuanınıv.

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0