

View Online at <https://aerobasegroup.com/nsn/5930-01-050-7162>

**Thread Class:**

2b single mounting facility

**Hazardous Locations/environmental Protection:**

Oil resistant

**Overall Length:**

3.400 inches

**Overall Height:**

1.255 inches

**Overall Width:**

1.620 inches

**Individual Section Quantity:**

1

**Knob Manufacturer Code:**

95146

**Knob Specification Markings:**

Arrow

**Longest Horizontal Distance Between Mounting Centers:**

0.750 inches single mounting facility

**Operating Temperature Range:**

-20.0/+50.0 degrees celsius

**Switch Contact Basic Design:**

Pile-up

**Mounting Method:**

Threaded hole single mounting facility

**Features Provided:**

Actuator knob and cam actuated

**Thready Qty Per Inch (tpi):**

40 single mounting facility

**Pile-up Contact Form Arrangement:**

1a single switch single section in-line

**Thread Size:**

0.112 inches single mounting facility

**Contact Voltage Rating In Volts:**

250.0 highest ac voltage rating at sea level

**Mounting Facility Pattern:**

Two position in-line single mounting facility

**Cam Actuated Switch Contact Arrangement:**

1 pole, single throw, both positions maintained single switch single section in-line

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Terminal Type:**

Tab w/screw

**Contact Switching Action:**

Breaks before makes single section in-line

**Contact Load Current Rating:**

6.0 amperes resistive load highest ac voltage rating at sea level

**Precious Material And Location:**

Contacts silver

**Precious Material:**

Silver

**Style Designator:**

In-line, cam actuated

**Thread Series Designator:**

Unc single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0