NSN 5930-01-050-8215

0.11 differential point pounds per square inch

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-050-8215

Overall Length:
3.500 inches
Overall Height:
3.968 inches
Overall Width:
3.500 inches
Unthreaded Mounting Hole Diameter:
0.203 inches
Distance Between Mounting Facility Centers:
2.250 inches
End Application:
Servicing platform 04162
Pressure Switch Type:
Gage
Mounting Method:
Bracket and unthreaded hole
Features Provided:
Tamper proof cap
Thready Qty Per Inch (tpi):
14 single pressure connection
Contact Action Stimulus:
Increase
Proof Pressure:
10.00 pounds per square inch
Thread Size:
0.500 inches single pressure connection
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Wire lead
Contact Load Current Rating:
10.0 amperes inductive load second voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+0.14/+3.00 actuation point pounds per square inch and +0.03/+2.89 deactuation point pounds per square inch
Contact Adjustment Type:
External deactuation point screw and external actuation point screw
Contact Stimulus Rating:

NSN 5930-01-050-8215

Pressure Switch - Page 2 of 2



Contact Voltage Rating In Volts:

480.0 ac at sea level first voltage

Pressure Connector Type:

Plain, threaded internal single connection

Media For Which Designed:

Gas or liquid

Thread Series Designator:

Nps single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0