

View Online at <https://aerobasegroup.com/nsn/5930-01-050-8428>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.250 inches single mounting facility

**Overall Length:**

2.201 inches

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.312 inches single actuator

**Nonturn Device Radius:**

0.531 inches at 3: 00 o'clock

**Individual Section Quantity:**

2

**Nonturn Device Type:**

Tab at 3: 00 o'clock

**End Application:**

N00019 and 74 and c and 0538 37695

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section front

**Throw Quantity:**

32 each section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Rotor Through Connection Quantity:**

1 each section

**Switch Actuator Indexing Position Quantity:**

32 single actuator

**Shaft Type:**

Round single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

11.2 degrees single actuator

**Contact Load Current Rating:**

200.0 milliamperes resistive load dc at sea level

**Precious Material And Location:**

Terminals gold and contacts silver

**Precious Material:**

Gold and silver

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0