

View Online at <https://aerobasegroup.com/nsn/5930-01-050-8433>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof and explosion proof

Body Length:

1.660 inches

Body Width:

Between 0.490 inches and 0.550 inches

Body Height:

1.300 inches

Case Material:

Metal

Unthreaded Mounting Hole Diameter:

0.138 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.500 inches

Actuator Style:

Round

Actuator Diameter:

0.250 inches

Actuator Height:

0.330 inches

Actuator Free Position Height:

0.375 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

Training device 49956

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

15.0 ounces

Switch Actuating Force:

20.0 ounces

Actuator Movement:

Between 0.203 pretravel inches and 0.250 overtravel inches and 0.100 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 6.000 amperes inductive dc and 10.000 amperes motor ac

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0