

View Online at <https://aerobasegroup.com/nsn/5930-01-050-8434>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof and shock proof

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.500 inches

Body Length:

0.781 inches

Body Width:

0.250 inches

Body Height:

0.438 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.088 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.165 inches

Actuator Length:

0.125 inches

Actuator Style:

Rectangular

Actuator Height:

0.093 inches

Actuator Width:

0.125 inches

Actuator Free Position Height:

0.401 inches

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

End Application:

Test set 05371

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

2 pole, single throw, normally closed, momentary action single switch unit

Switch Release Force:

Between 1.5 ounces and 3.5 ounces

Switch Actuating Force:

Between 1.5 ounces and 3.5 ounces

Contact Load Current Rating At Maximum Rated Voltage:

3.000 amperes inductive dc and 5.000 amperes resistive ac

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0