

View Online at <https://aerobasegroup.com/nsn/5930-01-051-1260>

Inside Diameter:

0.250 inches single connection

Thread Length:

0.688 inches single pressure connection

Overall Height:

1.938 inches

Overall Width:

1.938 inches

Longest Horizontal Distance Between Mounting Centers:

1.436 inches

Longest Vertical Distance Between Mounting Centers:

1.436 inches

Pressure Switch Type:

Gage

Mounting Method:

Flange and unthreaded hole and inlet connection

Proof Pressure:

1000.00 pounds per square inch gage

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

10.0 amperes resistive load second voltage

Contact Adjustability:

Actuation point adjustable and deactuation point adjustable

Contact Adjustment Range:

+3.50/+90.00 actuation point pounds per square inch gage and +3.00/+82.00 deactuation point pounds per square inch gage

Contact Adjustment Type:

External actuation point hex nut and external deactuation point hex nut

Contact Voltage Rating In Volts:

480.0 ac at sea level third voltage

Pressure Connector Type:

Plain, threaded internal single connection

Media For Which Designed:

Gas

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0