## NSN 5930-01-051-1268

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-051-1268

Thread Class:

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

**Overall Length:** 

1.812 inches

**Overall Height:** 

2.328 inches

**Overall Width:** 

1.984 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.218 inches single actuator

**Shaft Diameter:** 

0.248 inches single actuator and 0.251 inches single actuator

**Shaft Length:** 

0.312 inches single actuator

**Nonturn Device Radius:** 

0.531 inches at 9: 00 o'clock

**Individual Section Quantity:** 

2

**Nonturn Device Type:** 

Tab at 9: 00 o'clock

**End Application:** 

An/tcc-72 80058

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

**Pole Quantity:** 

1 each section front

**Throw Quantity:** 

24 each section rear

**Mounting Method:** 

Threaded bushing single mounting facility

**Thread Size:** 

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:** 

28.0 dc at sea level

**Rotor Through Connection Quantity:** 

1 each section

**Switch Actuator Indexing Position Quantity:** 

24 single actuator

## **NSN 5930-01-051-1268**Rotary Switch - Page 2 of 2



Shaft Type:
Round, flatted single actuator
Terminal Type:
Tab, solder lug
Contact Switching Action:
Breaks before makes each section rear
<b>Switch Actuator Positioning Increment</b>
15.0 degrees single actuator
Contact Load Current Rating:
1.0 amperes resistive load ac at sea level
Style Designator:
Circular wafer, bushing mount
Thread Series Designator:
Unef single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A052b0