# NSN 5930-01-051-5578

Sensitive Switch - Page 1 of 2

64.0 ounces



View Online at https://aerobasegroup.com/nsn/5930-01-051-5578

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Weatherproof
Overall Length:
3.625 inches
Overall Height:
1.875 inches
Case Material:
Metal
Actuator Length:
1.297 inches
Actuator Style:
Roller arm
Actuator Free Position Height:
1.375 inches
Actuator Roller Diameter:
0.500 inches
Actuator Roller Width:
0.188 inches
Housing Height:
1.250 inches
Housing Length:
2.500 inches
Housing Width:
1.219 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Height:
1.563 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
1.875 inches
Maximum Voltage Rating In Volts:
250.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
32.0 ounces
Switch Actuating Force:

## NSN 5930-01-051-5578

Sensitive Switch - Page 2 of 2



#### **Actuator Movement:**

Between 0.100 pretravel inches and 0.281 overtravel inches and 0.062 differential inches

#### **Contact Load Current Rating At Maximum Rated Voltage:**

15.000 amperes resistive dc and 10.000 amperes inductive dc and 10.000 amperes resistive ac

#### **Special Features:**

Connector polarizing keys at 105, 140, 215, and 265 degrees

### **Terminal Type And Quantity:**

1 connector, receptacle

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0