

View Online at <https://aerobasegroup.com/nsn/5930-01-051-5578>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Weatherproof

Overall Length:

3.625 inches

Overall Height:

1.875 inches

Case Material:

Metal

Actuator Length:

1.297 inches

Actuator Style:

Roller arm

Actuator Free Position Height:

1.375 inches

Actuator Roller Diameter:

0.500 inches

Actuator Roller Width:

0.188 inches

Housing Height:

1.250 inches

Housing Length:

2.500 inches

Housing Width:

1.219 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Height:

1.563 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

1.875 inches

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Features Provided:

Actuator seal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

32.0 ounces

Switch Actuating Force:

64.0 ounces

Actuator Movement:

Between 0.100 pretravel inches and 0.281 overtravel inches and 0.062 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive dc and 10.000 amperes inductive dc and 10.000 amperes resistive ac

Special Features:

Connector polarizing keys at 105, 140, 215, and 265 degrees

Terminal Type And Quantity:

1 connector, receptacle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0