

View Online at <https://aerobasegroup.com/nsn/5930-01-051-8955>

Overall Length:

5.312 inches

First Flat Length:

0.467 inches single actuator

Shaft Diameter:

2.498 inches single actuator and 2.502 inches single actuator

Overall Diameter:

1.900 inches

Individual Section Quantity:

5

Nonturn Device Type:

Key at 6: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

5 each section front

Throw Quantity:

5 each section front

Contact Voltage Rating In Volts:

28.0 dc at sea level

Rotor Through Connection Quantity:

5 each section

Cam Actuated Switch Contact Arrangement:

5 pole, single throw, both positions maintained each switch each section front

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Connector, receptacle

Contact Switching Action:

Makes before breaks, breaks before makes each section front

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Contact Load Current Rating:

5.0 amperes resistive load dc at sea level and 2.5 amperes inductive load dc at sea level

Style Designator:

Tap, circular, bushing mount

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A052b0