

View Online at <https://aerobasegroup.com/nsn/5930-01-051-9680>

Thread Class:

2b single mounting facility

Thread Length:

0.250 inches single mounting facility

Overall Length:

3.501 inches

Overall Height:

1.750 inches

Overall Width:

1.750 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.216 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.750 inches single actuator

Nonturn Device Radius:

0.531 inches at 12: 00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Tab at 12: 00 o'clock

Longest Horizontal Distance Between Mounting Centers:

1.375 inches single mounting facility

Operating Temperature Range:

-65.0/+125.0 degrees celsius

End Application:

Test adapter 13499

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

14 single section rear

Mounting Method:

Threaded hole single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Mounting Facility Pattern:

Two position in-line single mounting facility

Switch Actuator Indexing Position Quantity:

14 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

22.5 degrees single actuator

Detent Rotational Torque Range:

+1.500/+8.000 inch-pounds single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

500.0 milliamperes resistive load dc at sea level and 50.0 milliamperes inductive load dc at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0