

View Online at <https://aerobasegroup.com/nsn/5930-01-052-1259>

Thread Class:

2b single mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

2.460 inches

Overall Height:

4.220 inches

Overall Width:

1.540 inches

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.625 inches 1st actuator

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

1.160 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

2.340 inches single mounting facility

End Application:

Switch limit 27192

Switch Contact Basic Design:

Nonpile-up symmetrical

Mounting Method:

Bracket single mounting facility and threaded hole single mounting facility

Features Provided:

Cam actuated

Thread Size:

0.190 inches single mounting facility

Contact Voltage Rating In Volts:

240.0 ac at sea level

Mounting Facility Pattern:

Two position diagonal single mounting facility

Cam Actuated Switch Contact Arrangement:

3 pole, double throw, one position momentary single switch single section rear

Switch Actuator Indexing Position Quantity:

9 single actuator

Shaft Type:

Round, slotted single actuator

Terminal Type:

Screw

Contact Switching Action:

Breaks before makes single section rear

Contact Load Current Rating:

10.0 amperes resistive load ac at sea level

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0