

View Online at <https://aerobasegroup.com/nsn/5930-01-052-1259>

**Thread Class:**

2b single mounting facility

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

2.460 inches

**Overall Height:**

4.220 inches

**Overall Width:**

1.540 inches

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.625 inches 1st actuator

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

1.160 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

2.340 inches single mounting facility

**End Application:**

Switch limit 27192

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Mounting Method:**

Bracket single mounting facility and threaded hole single mounting facility

**Features Provided:**

Cam actuated

**Thread Size:**

0.190 inches single mounting facility

**Contact Voltage Rating In Volts:**

240.0 ac at sea level

**Mounting Facility Pattern:**

Two position diagonal single mounting facility

**Cam Actuated Switch Contact Arrangement:**

3 pole, double throw, one position momentary single switch single section rear

**Switch Actuator Indexing Position Quantity:**

9 single actuator

**Shaft Type:**

Round, slotted single actuator

**Terminal Type:**

Screw

**Contact Switching Action:**

Breaks before makes single section rear

**Contact Load Current Rating:**

10.0 amperes resistive load ac at sea level

**Style Designator:**

Tap, circuit selector

**Thread Series Designator:**

Unf single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0