# NSN 5930-01-052-1846

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-052-1846

# Body Style:

Hole mounted

#### Hazardous Locations/environmental Protection:

Dustproof

# Center To Center Distance Between Mounting Facilities Parallel To Length:

0.188 inches

#### Body Length:

0.500 inches

#### **Body Width:**

0.200 inches

#### **Body Height:**

0.343 inches

**Unthreaded Mounting Hole Diameter:** 

#### 0.096 inches

#### **Actuator Style:**

lotadio. oty

# Round

Actuator Diameter:

0.062 inches

## Actuator Height:

0.031 inches

#### **Actuator Free Position Height:**

0.343 inches

#### Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

#### Inclosure Type:

Hermetically sealed

#### **Mounting Method:**

Unthreaded hole

#### Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

#### Switch Release Force:

1.0 ounces

#### Switch Actuating Force:

5.0 ounces

#### **Actuator Movement:**

0.030 pretravel inches and 0.040 overtravel inches and 0.004 differential inches

## Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 7.000 amperes resistive ac

## Terminal Type And Quantity:

3 turret

#### Shelf Life:

N/a

# NSN 5930-01-052-1846

Sensitive Switch - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0

