## NSN 5930-01-052-3432

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-052-3432

3.400 inches Overall Height: 1.620 inches Overall Width: 1.255 inches Individual Section Quantity: 1 Knob Manufacturer Code: 95146 Knob Specificationial Markings: White arrow Operating Tempurature Range: -20.0/+50.0 degrees celsius Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method: Base single mounting facility Features Provided: Actuator knob and cam actuated Contact Voltage Rating In Volts: 250.0 highest ac voltage rating at sea level Cam Actuator Indexing Position Quantity: 2 single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes single section in-line Switch Actuator Positioning Increment: 90.0 degrees single actuator Contact Load Current Rating: 6.0 amperes resistive load highest ac voltage rating at sea level Special Features: Black actuator Style Designator:	3.400 inches Overall Height: 1.620 inches Overall Width: 1.255 inches Individual Section Quantity: 1 Knob Manufacturer Code: 95146 Knob Specificationial Markings: White arrow Operating Tempurature Range: -20.0/+50.0 degrees celsius Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method: Base single mounting facility Features Provided: Actuator knob and cam actuated Contact Voltage Rating In Volts: 250.0 highest ac voltage rating at sea level Cam Actuated Switch Contact Arrangement: 1 pole, double throw, both positions maintained single switch single section in-line Switch Actuator Indexing Position Quantity: 2 single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes single section in-line Switch Actuator Positioning Increment: 90.0 degrees single actuator Contact Load Current Rating: 6.0 amperes resistive load highest ac voltage rating at sea level Special Features: Black actuator	Overall Length:
Overall Height: 1.620 inches Overall Width: 1.255 inches Individual Section Quantity: 1 Knob Manufacturer Code: 95146 Knob Specificationial Markings: White arrow Operating Tempurature Range: -20.0/+50.0 degrees celsius Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method: Base single mounting facility Features Provided: Actuator knob and cam actuated Contact Voltage Rating In Volts: 250.0 highest ac voltage rating at sea level Cam Actuated Switch Contact Arrangement: 1 pole, double throw, both positions maintained single switch single section in-line Switch Actuator Indexing Position Quantity: 2 single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes single section in-line Switch Actuator Positioning Increment: 90.0 degrees single actuator Contact Load Current Rating: 6.0 amperes resistive load highest ac voltage rating at sea level Special Features: Black actuator Style Designator:	Overall Height:  1.620 inches  Overall Width:  1.255 inches  Individual Section Quantity:  1  Knob Manufacturer Code: 95146  Knob Specificationial Markings: White arrow  Operating Tempurature Range: -20.0/+50.0 degrees celsius  Switch Contact Basic Design: Nonpile-up nonsymmetrical  Mounting Method: Base single mounting facility  Features Provided: Actuator knob and cam actuated  Contact Voltage Rating In Volts: 250.0 highest ac voltage rating at sea level  Cam Actuated Switch Contact Arrangement: 1 pole, double throw, both positions maintained single switch single section in-line  Switch Actuator Indexing Position Quantity: 2 single actuator  Terminal Type:  Tab w/screw  Contact Switching Action: Breaks before makes single section in-line  Switch Actuator Positioning Increment: 90.0 degrees single actuator  Contact Load Current Rating: 6.0 amperes resistive load highest ac voltage rating at sea level  Special Features: Black actuator  Style Designator: In-line, cam actuated  Shelf Life: N/a	-
1.620 inches Overall Width: 1.255 inches Individual Section Quantity: 1 Knob Manufacturer Code: 95146 Knob Specificationial Markings: White arrow Operating Tempurature Range: -20.0/+50.0 degrees celsius Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method: Base single mounting facility Features Provided: Actuator knob and cam actuated Contact Voltage Rating In Volts: 250.0 highest ac voltage rating at sea level Cam Actuated Switch Contact Arrangement: 1 pole, double throw, both positions maintained single switch single section in-line Switch Actuator Indexing Position Quantity: 2 single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes single section in-line Switch Actuator Positioning Increment: 90.0 degrees single actuator Contact Load Current Rating: 6.0 amperes resistive load highest ac voltage rating at sea level Special Features: Black actuator Style Designator:	1.620 inches Overall Width: 1.255 inches Individual Section Quantity: 1 Knob Manufacturer Code: 95146 Knob Specificationial Markings: White arrow Operating Tempurature Range: -20.0/+50.0 degrees celsius Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method: Base single mounting facility Features Provided: Actuator knob and cam actuated Contact Voltage Rating In Volts: 250.0 highest ac voltage rating at sea level Cam Actuated Switch Contact Arrangement: 1 pole, double throw, both positions maintained single switch single section in-line Switch Actuator Indexing Position Quantity: 2 single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes single section in-line Switch Actuator Positioning Increment: 90.0 degrees single actuator Contact Load Current Rating: 6.0 amperes resistive load highest ac voltage rating at sea level Special Features: Black actuator Style Designator: In-line, cam actuated Shelf Life: N/a	
Overall Width:  1.255 inches Individual Section Quantity:  1 Knob Manufacturer Code: 95146 Knob Specificationial Markings: White arrow Operating Tempurature Range: -20.0/+50.0 degrees celsius Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method: Base single mounting facility Features Provided: Actuator knob and cam actuated Contact Voltage Rating In Volts: 250.0 highest ac voltage rating at sea level Cam Actuated Switch Contact Arrangement: 1 pole, double throw, both positions maintained single switch single section in-line Switch Actuator Indexing Position Quantity: 2 single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes single section in-line Switch Actuator Positioning Increment: 90.0 degrees single actuator Contact Load Current Rating: 6.0 amperes resistive load highest ac voltage rating at sea level Special Features: Black actuator Style Designator:	Overall Width:  1.255 inches Individual Section Quantity:  1 Knob Manufacturer Code: 95146 Knob Specificationial Markings: White arrow Operating Tempurature Range: -20.0/+50.0 degrees celsius Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method: Base single mounting facility Features Provided: Actuator knob and cam actuated Contact Voltage Rating In Volts: 250.0 highest ac voltage rating at sea level Cam Actuated Switch Contact Arrangement: 1 pole, double throw, both positions maintained single switch single section in-line Switch Actuator Indexing Position Quantity: 2 single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes single section in-line Switch Actuator Positioning Increment: 90.0 degrees single actuator Contact Load Current Rating: 6.0 amperes resistive load highest ac voltage rating at sea level Special Features: Black actuator Style Designator: In-line, cam actuated Shelf Life: N/a	-
Individual Section Quantity:  1 Knob Manufacturer Code: 95146 Knob Specificationial Markings: White arrow Operating Tempurature Range: -20.0/+50.0 degrees celsius Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method: Base single mounting facility Features Provided: Actuator knob and cam actuated Contact Voltage Rating In Volts: 250.0 highest ac voltage rating at sea level Cam Actuated Switch Contact Arrangement: 1 pole, double throw, both positions maintained single switch single section in-line Switch Actuator Indexing Position Quantity: 2 single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes single section in-line Switch Actuator Positioning Increment: 90.0 degrees single actuator Contact Load Current Rating: 6.0 amperes resistive load highest ac voltage rating at sea level Special Features: Black actuator Style Designator:	Individual Section Quantity:  1 Knob Manufacturer Code: 95146 Knob Specificationial Markings: White arrow Operating Tempurature Range: -20.0/+50.0 degrees celsius Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method: Base single mounting facility Features Provided: Actuator knob and cam actuated Contact Voltage Rating In Volts: 250.0 highest ac voltage rating at sea level Cam Actuated Switch Contact Arrangement: 1 pole, double throw, both positions maintained single switch single section in-line Switch Actuator Indexing Position Quantity: 2 single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes single section in-line Switch Actuator Positioning Increment: 90.0 degrees single actuator Contact Load Current Rating: 6.0 amperes resistive load highest ac voltage rating at sea level Special Features: Black actuator Style Designator: In-line, cam actuated Shelf Life: N/a	
Individual Section Quantity:  1 Knob Manufacturer Code: 95146 Knob Specificationial Markings: White arrow Operating Tempurature Range: -20.0/+50.0 degrees celsius Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method: Base single mounting facility Features Provided: Actuator knob and cam actuated Contact Voltage Rating In Volts: 250.0 highest ac voltage rating at sea level Cam Actuated Switch Contact Arrangement: 1 pole, double throw, both positions maintained single switch single section in-line Switch Actuator Indexing Position Quantity: 2 single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes single section in-line Switch Actuator Positioning Increment: 90.0 degrees single actuator Contact Load Current Rating: 6.0 amperes resistive load highest ac voltage rating at sea level Special Features: Black actuator Style Designator:	Individual Section Quantity:  Knob Manufacturer Code: 95146 Knob Specificationial Markings: White arrow Operating Tempurature Range: -20.0/+50.0 degrees celsius Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method: Base single mounting facility Features Provided: Actuator knob and cam actuated Contact Voltage Rating In Volts: 250.0 highest ac voltage rating at sea level Cam Actuated Switch Contact Arrangement: 1 pole, double throw, both positions maintained single switch single section in-line Switch Actuator Indexing Position Quantity: 2 single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes single section in-line Switch Actuator Positioning Increment: 90.0 degrees single actuator Contact Load Current Rating: 6.0 amperes resistive load highest ac voltage rating at sea level Special Features: Black actuator Style Designator: In-line, cam actuated Shelf Life: N/a	
Knob Manufacturer Code: 95146 Knob Specificationial Markings: White arrow Operating Tempurature Range: -20.0/+50.0 degrees celsius Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method: Base single mounting facility Features Provided: Actuator knob and cam actuated Contact Voltage Rating In Volts: 250.0 highest ac voltage rating at sea level Cam Actuated Switch Contact Arrangement: 1 pole, double throw, both positions maintained single switch single section in-line Switch Actuator Indexing Position Quantity: 2 single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes single section in-line Switch Actuator Positioning Increment: 90.0 degrees single actuator Contact Load Current Rating: 6.0 amperes resistive load highest ac voltage rating at sea level Special Features: Black actuator Style Designator:	Knob Manufacturer Code: 95146 Knob Specificationial Markings: White arrow Operating Tempurature Range: -20.0/+50.0 degrees celsius Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method: Base single mounting facility Features Provided: Actuator knob and cam actuated Contact Voltage Rating In Volts: 250.0 highest ac voltage rating at sea level Cam Actuated Switch Contact Arrangement: 1 pole, double throw, both positions maintained single switch single section in-line Switch Actuator Indexing Position Quantity: 2 single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes single section in-line Switch Actuator Positioning Increment: 90.0 degrees single actuator Contact Load Current Rating: 6.0 amperes resistive load highest ac voltage rating at sea level Special Features: Black actuator Style Designator: In-line, cam actuated Shelf Life: N/a	
Knob Manufacturer Code: 95146 Knob Specificationial Markings: White arrow Operating Tempurature Range: -20.0/+50.0 degrees celsius Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method: Base single mounting facility Features Provided: Actuator knob and cam actuated Contact Voltage Rating In Volts: 250.0 highest ac voltage rating at sea level Cam Actuated Switch Contact Arrangement: 1 pole, double throw, both positions maintained single switch single section in-line Switch Actuator Indexing Position Quantity: 2 single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes single section in-line Switch Actuator Positioning Increment: 90.0 degrees single actuator Contact Load Current Rating: 6.0 amperes resistive load highest ac voltage rating at sea level Special Features: Black actuator Style Designator:	Knob Manufacturer Code: 95146 Knob Specificationial Markings: White arrow Operating Tempurature Range: -20.0/+50.0 degrees celsius Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method: Base single mounting facility Features Provided: Actuator knob and cam actuated Contact Voltage Rating In Volts: 250.0 highest ac voltage rating at sea level Cam Actuated Switch Contact Arrangement: 1 pole, double throw, both positions maintained single switch single section in-line Switch Actuator Indexing Position Quantity: 2 single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes single section in-line Switch Actuator Positioning Increment: 90.0 degrees single actuator Contact Load Current Rating: 6.0 amperes resistive load highest ac voltage rating at sea level Special Features: Black actuator Style Designator: In-line, cam actuated Shelf Life: N/a	
95146 Knob Specificationial Markings: White arrow Operating Tempurature Range: -20.0/+50.0 degrees celsius Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method: Base single mounting facility Features Provided: Actuator knob and cam actuated Contact Voltage Rating In Volts: 250.0 highest ac voltage rating at sea level Cam Actuated Switch Contact Arrangement: 1 pole, double throw, both positions maintained single switch single section in-line Switch Actuator Indexing Position Quantity: 2 single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes single section in-line Switch Actuator Positioning Increment: 90.0 degrees single actuator Contact Load Current Rating: 6.0 amperes resistive load highest ac voltage rating at sea level Special Features: Black actuator Style Designator:	95146 Knob Specificationial Markings: White arrow Operating Tempurature Range: -20.0/+50.0 degrees celsius Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method: Base single mounting facility Features Provided: Actuator knob and cam actuated Contact Voltage Rating In Volts: 250.0 highest ac voltage rating at sea level Cam Actuated Switch Contact Arrangement: 1 pole, double throw, both positions maintained single switch single section in-line Switch Actuator Indexing Position Quantity: 2 single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes single section in-line Switch Actuator Positioning Increment: 90.0 degrees single actuator Contact Load Current Rating: 6.0 amperes resistive load highest ac voltage rating at sea level Special Features: Black actuator Style Designator: In-line, cam actuated Shelf Life: N/a	
Knob Specificationial Markings:  White arrow  Operating Tempurature Range: -20.0/+50.0 degrees celsius  Switch Contact Basic Design:  Nonpile-up nonsymmetrical  Mounting Method: Base single mounting facility  Features Provided: Actuator knob and cam actuated  Contact Voltage Rating In Volts: 250.0 highest ac voltage rating at sea level  Cam Actuated Switch Contact Arrangement: 1 pole, double throw, both positions maintained single switch single section in-line  Switch Actuator Indexing Position Quantity: 2 single actuator  Terminal Type: Tab w/screw  Contact Switching Action:  Breaks before makes single section in-line  Switch Actuator Positioning Increment: 90.0 degrees single actuator  Contact Load Current Rating: 6.0 amperes resistive load highest ac voltage rating at sea level  Special Features: Black actuator  Style Designator:	Knob Specificationial Markings:  White arrow  Operating Tempurature Range: -20.0/+50.0 degrees celsius  Switch Contact Basic Design:  Nonpile-up nonsymmetrical  Mounting Method: Base single mounting facility  Features Provided: Actuator knob and cam actuated  Contact Voltage Rating In Volts: 250.0 highest ac voltage rating at sea level  Cam Actuated Switch Contact Arrangement: 1 pole, double throw, both positions maintained single switch single section in-line  Switch Actuator Indexing Position Quantity: 2 single actuator  Terminal Type: Tab w/screw  Contact Switching Action:  Breaks before makes single section in-line  Switch Actuator Positioning Increment: 90.0 degrees single actuator  Contact Load Current Rating: 6.0 amperes resistive load highest ac voltage rating at sea level  Special Features: Black actuator  Style Designator: In-line, cam actuated  Shelf Life: N/a	
White arrow  Operating Tempurature Range: -20.0/+50.0 degrees celsius  Switch Contact Basic Design: Nonpile-up nonsymmetrical  Mounting Method: Base single mounting facility  Features Provided: Actuator knob and cam actuated  Contact Voltage Rating In Volts: 250.0 highest ac voltage rating at sea level  Cam Actuated Switch Contact Arrangement: 1 pole, double throw, both positions maintained single switch single section in-line  Switch Actuator Indexing Position Quantity: 2 single actuator  Terminal Type: Tab w/screw  Contact Switching Action: Breaks before makes single section in-line  Switch Actuator Positioning Increment: 90.0 degrees single actuator  Contact Load Current Rating: 6.0 amperes resistive load highest ac voltage rating at sea level  Special Features: Black actuator  Style Designator:	White arrow  Operating Tempurature Range: -20.0/+50.0 degrees celsius  Switch Contact Basic Design: Nonpile-up nonsymmetrical  Mounting Method: Base single mounting facility  Features Provided: Actuator knob and cam actuated  Contact Voltage Rating In Volts: 250.0 highest ac voltage rating at sea level  Cam Actuated Switch Contact Arrangement: 1 pole, double throw, both positions maintained single switch single section in-line  Switch Actuator Indexing Position Quantity: 2 single actuator  Terminal Type: Tab w/screw  Contact Switching Action: Breaks before makes single section in-line  Switch Actuator Positioning Increment: 90.0 degrees single actuator  Contact Load Current Rating: 6.0 amperes resistive load highest ac voltage rating at sea level  Special Features: Black actuator  Style Designator: In-line, cam actuated  Shelf Life: N/a	
Operating Tempurature Range: -20.0/+50.0 degrees celsius Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method: Base single mounting facility Features Provided: Actuator knob and cam actuated Contact Voltage Rating In Volts: 250.0 highest ac voltage rating at sea level Cam Actuated Switch Contact Arrangement: 1 pole, double throw, both positions maintained single switch single section in-line Switch Actuator Indexing Position Quantity: 2 single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes single section in-line Switch Actuator Positioning Increment: 90.0 degrees single actuator Contact Load Current Rating: 6.0 amperes resistive load highest ac voltage rating at sea level Special Features: Black actuator Style Designator:	Operating Tempurature Range: -20.0/+50.0 degrees celsius Switch Contact Basic Design: Nonpile-up nonsymmetrical Mounting Method: Base single mounting facility Features Provided: Actuator knob and cam actuated Contact Voltage Rating In Volts: 250.0 highest ac voltage rating at sea level Cam Actuated Switch Contact Arrangement: 1 pole, double throw, both positions maintained single switch single section in-line Switch Actuator Indexing Position Quantity: 2 single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes single section in-line Switch Actuator Positioning Increment: 90.0 degrees single actuator Contact Load Current Rating: 6.0 amperes resistive load highest ac voltage rating at sea level Special Features: Black actuator Style Designator: In-line, cam actuated Shelf Life: N/a	
-20.0/+50.0 degrees celsius  Switch Contact Basic Design: Nonpile-up nonsymmetrical  Mounting Method: Base single mounting facility  Features Provided: Actuator knob and cam actuated  Contact Voltage Rating In Volts: 250.0 highest ac voltage rating at sea level  Cam Actuated Switch Contact Arrangement: 1 pole, double throw, both positions maintained single switch single section in-line  Switch Actuator Indexing Position Quantity: 2 single actuator  Terminal Type: Tab w/screw  Contact Switching Action: Breaks before makes single section in-line  Switch Actuator Positioning Increment: 90.0 degrees single actuator  Contact Load Current Rating: 6.0 amperes resistive load highest ac voltage rating at sea level  Special Features: Black actuator  Style Designator:	-20.0/+50.0 degrees celsius  Switch Contact Basic Design: Nonpile-up nonsymmetrical  Mounting Method: Base single mounting facility  Features Provided: Actuator knob and cam actuated  Contact Voltage Rating In Volts: 250.0 highest ac voltage rating at sea level  Cam Actuated Switch Contact Arrangement: 1 pole, double throw, both positions maintained single switch single section in-line  Switch Actuator Indexing Position Quantity: 2 single actuator  Terminal Type: Tab w/screw  Contact Switching Action: Breaks before makes single section in-line  Switch Actuator Positioning Increment: 90.0 degrees single actuator  Contact Load Current Rating: 6.0 amperes resistive load highest ac voltage rating at sea level  Special Features: Black actuator  Style Designator: In-line, cam actuated  Shelf Life: N/a	
Switch Contact Basic Design:  Nonpile-up nonsymmetrical  Mounting Method:  Base single mounting facility  Features Provided:  Actuator knob and cam actuated  Contact Voltage Rating In Volts:  250.0 highest ac voltage rating at sea level  Cam Actuated Switch Contact Arrangement:  1 pole, double throw, both positions maintained single switch single section in-line  Switch Actuator Indexing Position Quantity:  2 single actuator  Terminal Type:  Tab w/screw  Contact Switching Action:  Breaks before makes single section in-line  Switch Actuator Positioning Increment:  90.0 degrees single actuator  Contact Load Current Rating:  6.0 amperes resistive load highest ac voltage rating at sea level  Special Features:  Black actuator  Style Designator:	Switch Contact Basic Design:  Nonpile-up nonsymmetrical  Mounting Method:  Base single mounting facility  Features Provided:  Actuator knob and cam actuated  Contact Voltage Rating In Volts:  250.0 highest ac voltage rating at sea level  Cam Actuated Switch Contact Arrangement:  1 pole, double throw, both positions maintained single switch single section in-line  Switch Actuator Indexing Position Quantity:  2 single actuator  Terminal Type:  Tab w/screw  Contact Switching Action:  Breaks before makes single section in-line  Switch Actuator Positioning Increment:  90.0 degrees single actuator  Contact Load Current Rating:  6.0 amperes resistive load highest ac voltage rating at sea level  Special Features:  Black actuator  Style Designator:  In-line, cam actuated  Shelf Life:  N/a	
Nonpile-up nonsymmetrical  Mounting Method: Base single mounting facility  Features Provided: Actuator knob and cam actuated  Contact Voltage Rating In Volts: 250.0 highest ac voltage rating at sea level  Cam Actuated Switch Contact Arrangement: 1 pole, double throw, both positions maintained single switch single section in-line  Switch Actuator Indexing Position Quantity: 2 single actuator  Terminal Type: Tab w/screw  Contact Switching Action: Breaks before makes single section in-line  Switch Actuator Positioning Increment: 90.0 degrees single actuator  Contact Load Current Rating: 6.0 amperes resistive load highest ac voltage rating at sea level  Special Features: Black actuator  Style Designator:	Nonpile-up nonsymmetrical  Mounting Method: Base single mounting facility  Features Provided: Actuator knob and cam actuated  Contact Voltage Rating In Volts: 250.0 highest ac voltage rating at sea level  Cam Actuated Switch Contact Arrangement: 1 pole, double throw, both positions maintained single switch single section in-line  Switch Actuator Indexing Position Quantity: 2 single actuator  Terminal Type: Tab w/screw  Contact Switching Action: Breaks before makes single section in-line  Switch Actuator Positioning Increment: 90.0 degrees single actuator  Contact Load Current Rating: 6.0 amperes resistive load highest ac voltage rating at sea level  Special Features: Black actuator  Style Designator: In-line, cam actuated  Shelf Life: N/a	•
Mounting Method: Base single mounting facility Features Provided: Actuator knob and cam actuated Contact Voltage Rating In Volts: 250.0 highest ac voltage rating at sea level Cam Actuated Switch Contact Arrangement: 1 pole, double throw, both positions maintained single switch single section in-line Switch Actuator Indexing Position Quantity: 2 single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes single section in-line Switch Actuator Positioning Increment: 90.0 degrees single actuator Contact Load Current Rating: 6.0 amperes resistive load highest ac voltage rating at sea level Special Features: Black actuator Style Designator:	Mounting Method: Base single mounting facility Features Provided: Actuator knob and cam actuated Contact Voltage Rating In Volts: 250.0 highest ac voltage rating at sea level Cam Actuated Switch Contact Arrangement: 1 pole, double throw, both positions maintained single switch single section in-line Switch Actuator Indexing Position Quantity: 2 single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes single section in-line Switch Actuator Positioning Increment: 90.0 degrees single actuator Contact Load Current Rating: 6.0 amperes resistive load highest ac voltage rating at sea level Special Features: Black actuator Style Designator: In-line, cam actuated Shelf Life: N/a	
Base single mounting facility  Features Provided: Actuator knob and cam actuated  Contact Voltage Rating In Volts: 250.0 highest ac voltage rating at sea level  Cam Actuated Switch Contact Arrangement: 1 pole, double throw, both positions maintained single switch single section in-line  Switch Actuator Indexing Position Quantity: 2 single actuator  Terminal Type: Tab w/screw  Contact Switching Action: Breaks before makes single section in-line  Switch Actuator Positioning Increment: 90.0 degrees single actuator  Contact Load Current Rating: 6.0 amperes resistive load highest ac voltage rating at sea level  Special Features: Black actuator  Style Designator:	Base single mounting facility  Features Provided: Actuator knob and cam actuated  Contact Voltage Rating In Volts: 250.0 highest ac voltage rating at sea level  Cam Actuated Switch Contact Arrangement: 1 pole, double throw, both positions maintained single switch single section in-line  Switch Actuator Indexing Position Quantity: 2 single actuator  Terminal Type: Tab w/screw  Contact Switching Action: Breaks before makes single section in-line  Switch Actuator Positioning Increment: 90.0 degrees single actuator  Contact Load Current Rating: 6.0 amperes resistive load highest ac voltage rating at sea level  Special Features: Black actuator  Style Designator: In-line, cam actuated  Shelf Life: N/a	
Features Provided: Actuator knob and cam actuated Contact Voltage Rating In Volts: 250.0 highest ac voltage rating at sea level Cam Actuated Switch Contact Arrangement: 1 pole, double throw, both positions maintained single switch single section in-line Switch Actuator Indexing Position Quantity: 2 single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes single section in-line Switch Actuator Positioning Increment: 90.0 degrees single actuator Contact Load Current Rating: 6.0 amperes resistive load highest ac voltage rating at sea level Special Features: Black actuator Style Designator:	Features Provided: Actuator knob and cam actuated Contact Voltage Rating In Volts: 250.0 highest ac voltage rating at sea level Cam Actuated Switch Contact Arrangement: 1 pole, double throw, both positions maintained single switch single section in-line Switch Actuator Indexing Position Quantity: 2 single actuator Terminal Type: Tab w/screw Contact Switching Action: Breaks before makes single section in-line Switch Actuator Positioning Increment: 90.0 degrees single actuator Contact Load Current Rating: 6.0 amperes resistive load highest ac voltage rating at sea level Special Features: Black actuator Style Designator: In-line, cam actuated Shelf Life: N/a	
Actuator knob and cam actuated  Contact Voltage Rating In Volts:  250.0 highest ac voltage rating at sea level  Cam Actuated Switch Contact Arrangement:  1 pole, double throw, both positions maintained single switch single section in-line  Switch Actuator Indexing Position Quantity:  2 single actuator  Terminal Type:  Tab w/screw  Contact Switching Action:  Breaks before makes single section in-line  Switch Actuator Positioning Increment:  90.0 degrees single actuator  Contact Load Current Rating:  6.0 amperes resistive load highest ac voltage rating at sea level  Special Features:  Black actuator  Style Designator:	Actuator knob and cam actuated  Contact Voltage Rating In Volts:  250.0 highest ac voltage rating at sea level  Cam Actuated Switch Contact Arrangement:  1 pole, double throw, both positions maintained single switch single section in-line  Switch Actuator Indexing Position Quantity:  2 single actuator  Terminal Type:  Tab w/screw  Contact Switching Action:  Breaks before makes single section in-line  Switch Actuator Positioning Increment:  90.0 degrees single actuator  Contact Load Current Rating:  6.0 amperes resistive load highest ac voltage rating at sea level  Special Features:  Black actuator  Style Designator:  In-line, cam actuated  Shelf Life:  N/a	
Contact Voltage Rating In Volts:  250.0 highest ac voltage rating at sea level  Cam Actuated Switch Contact Arrangement:  1 pole, double throw, both positions maintained single switch single section in-line  Switch Actuator Indexing Position Quantity:  2 single actuator  Terminal Type:  Tab w/screw  Contact Switching Action:  Breaks before makes single section in-line  Switch Actuator Positioning Increment:  90.0 degrees single actuator  Contact Load Current Rating:  6.0 amperes resistive load highest ac voltage rating at sea level  Special Features:  Black actuator  Style Designator:	Contact Voltage Rating In Volts:  250.0 highest ac voltage rating at sea level  Cam Actuated Switch Contact Arrangement:  1 pole, double throw, both positions maintained single switch single section in-line  Switch Actuator Indexing Position Quantity:  2 single actuator  Terminal Type:  Tab w/screw  Contact Switching Action:  Breaks before makes single section in-line  Switch Actuator Positioning Increment:  90.0 degrees single actuator  Contact Load Current Rating:  6.0 amperes resistive load highest ac voltage rating at sea level  Special Features:  Black actuator  Style Designator:  In-line, cam actuated  Shelf Life:  N/a	
250.0 highest ac voltage rating at sea level  Cam Actuated Switch Contact Arrangement:  1 pole, double throw, both positions maintained single switch single section in-line  Switch Actuator Indexing Position Quantity:  2 single actuator  Terminal Type:  Tab w/screw  Contact Switching Action:  Breaks before makes single section in-line  Switch Actuator Positioning Increment:  90.0 degrees single actuator  Contact Load Current Rating:  6.0 amperes resistive load highest ac voltage rating at sea level  Special Features:  Black actuator  Style Designator:	250.0 highest ac voltage rating at sea level  Cam Actuated Switch Contact Arrangement:  1 pole, double throw, both positions maintained single switch single section in-line  Switch Actuator Indexing Position Quantity:  2 single actuator  Terminal Type:  Tab w/screw  Contact Switching Action:  Breaks before makes single section in-line  Switch Actuator Positioning Increment:  90.0 degrees single actuator  Contact Load Current Rating:  6.0 amperes resistive load highest ac voltage rating at sea level  Special Features:  Black actuator  Style Designator:  In-line, cam actuated  Shelf Life:  N/a	
Cam Actuated Switch Contact Arrangement:  1 pole, double throw, both positions maintained single switch single section in-line  Switch Actuator Indexing Position Quantity:  2 single actuator  Terminal Type:  Tab w/screw  Contact Switching Action:  Breaks before makes single section in-line  Switch Actuator Positioning Increment:  90.0 degrees single actuator  Contact Load Current Rating:  6.0 amperes resistive load highest ac voltage rating at sea level  Special Features:  Black actuator  Style Designator:	Cam Actuated Switch Contact Arrangement:  1 pole, double throw, both positions maintained single switch single section in-line  Switch Actuator Indexing Position Quantity:  2 single actuator  Terminal Type:  Tab w/screw  Contact Switching Action:  Breaks before makes single section in-line  Switch Actuator Positioning Increment:  90.0 degrees single actuator  Contact Load Current Rating:  6.0 amperes resistive load highest ac voltage rating at sea level  Special Features:  Black actuator  Style Designator:  In-line, cam actuated  Shelf Life:  N/a	
1 pole, double throw, both positions maintained single switch single section in-line  Switch Actuator Indexing Position Quantity:  2 single actuator  Terminal Type:  Tab w/screw  Contact Switching Action:  Breaks before makes single section in-line  Switch Actuator Positioning Increment:  90.0 degrees single actuator  Contact Load Current Rating:  6.0 amperes resistive load highest ac voltage rating at sea level  Special Features:  Black actuator  Style Designator:	1 pole, double throw, both positions maintained single switch single section in-line  Switch Actuator Indexing Position Quantity:  2 single actuator  Terminal Type:  Tab w/screw  Contact Switching Action:  Breaks before makes single section in-line  Switch Actuator Positioning Increment:  90.0 degrees single actuator  Contact Load Current Rating:  6.0 amperes resistive load highest ac voltage rating at sea level  Special Features:  Black actuator  Style Designator:  In-line, cam actuated  Shelf Life:  N/a	
Switch Actuator Indexing Position Quantity:  2 single actuator  Terminal Type:  Tab w/screw  Contact Switching Action:  Breaks before makes single section in-line  Switch Actuator Positioning Increment:  90.0 degrees single actuator  Contact Load Current Rating:  6.0 amperes resistive load highest ac voltage rating at sea level  Special Features:  Black actuator  Style Designator:	Switch Actuator Indexing Position Quantity:  2 single actuator  Terminal Type:  Tab w/screw  Contact Switching Action:  Breaks before makes single section in-line  Switch Actuator Positioning Increment:  90.0 degrees single actuator  Contact Load Current Rating:  6.0 amperes resistive load highest ac voltage rating at sea level  Special Features:  Black actuator  Style Designator:  In-line, cam actuated  Shelf Life:  N/a	-
2 single actuator  Terminal Type: Tab w/screw  Contact Switching Action: Breaks before makes single section in-line  Switch Actuator Positioning Increment: 90.0 degrees single actuator  Contact Load Current Rating: 6.0 amperes resistive load highest ac voltage rating at sea level  Special Features: Black actuator  Style Designator:	2 single actuator  Terminal Type:  Tab w/screw  Contact Switching Action:  Breaks before makes single section in-line  Switch Actuator Positioning Increment:  90.0 degrees single actuator  Contact Load Current Rating:  6.0 amperes resistive load highest ac voltage rating at sea level  Special Features:  Black actuator  Style Designator:  In-line, cam actuated  Shelf Life:  N/a	
Terminal Type: Tab w/screw  Contact Switching Action: Breaks before makes single section in-line  Switch Actuator Positioning Increment: 90.0 degrees single actuator  Contact Load Current Rating: 6.0 amperes resistive load highest ac voltage rating at sea level  Special Features: Black actuator  Style Designator:	Terminal Type: Tab w/screw  Contact Switching Action: Breaks before makes single section in-line  Switch Actuator Positioning Increment: 90.0 degrees single actuator  Contact Load Current Rating: 6.0 amperes resistive load highest ac voltage rating at sea level  Special Features: Black actuator  Style Designator: In-line, cam actuated  Shelf Life: N/a	
Tab w/screw  Contact Switching Action: Breaks before makes single section in-line  Switch Actuator Positioning Increment: 90.0 degrees single actuator  Contact Load Current Rating: 6.0 amperes resistive load highest ac voltage rating at sea level  Special Features: Black actuator  Style Designator:	Tab w/screw  Contact Switching Action: Breaks before makes single section in-line  Switch Actuator Positioning Increment: 90.0 degrees single actuator  Contact Load Current Rating: 6.0 amperes resistive load highest ac voltage rating at sea level  Special Features: Black actuator  Style Designator: In-line, cam actuated  Shelf Life: N/a	S .
Breaks before makes single section in-line  Switch Actuator Positioning Increment:  90.0 degrees single actuator  Contact Load Current Rating:  6.0 amperes resistive load highest ac voltage rating at sea level  Special Features:  Black actuator  Style Designator:	Breaks before makes single section in-line  Switch Actuator Positioning Increment:  90.0 degrees single actuator  Contact Load Current Rating:  6.0 amperes resistive load highest ac voltage rating at sea level  Special Features:  Black actuator  Style Designator:  In-line, cam actuated  Shelf Life:  N/a	
Breaks before makes single section in-line  Switch Actuator Positioning Increment:  90.0 degrees single actuator  Contact Load Current Rating:  6.0 amperes resistive load highest ac voltage rating at sea level  Special Features:  Black actuator  Style Designator:	Breaks before makes single section in-line  Switch Actuator Positioning Increment:  90.0 degrees single actuator  Contact Load Current Rating:  6.0 amperes resistive load highest ac voltage rating at sea level  Special Features:  Black actuator  Style Designator:  In-line, cam actuated  Shelf Life:  N/a	Contact Switching Action:
Switch Actuator Positioning Increment:  90.0 degrees single actuator  Contact Load Current Rating: 6.0 amperes resistive load highest ac voltage rating at sea level  Special Features:  Black actuator  Style Designator:	Switch Actuator Positioning Increment:  90.0 degrees single actuator  Contact Load Current Rating: 6.0 amperes resistive load highest ac voltage rating at sea level  Special Features:  Black actuator  Style Designator:  In-line, cam actuated  Shelf Life:  N/a	
90.0 degrees single actuator  Contact Load Current Rating: 6.0 amperes resistive load highest ac voltage rating at sea level  Special Features: Black actuator  Style Designator:	90.0 degrees single actuator  Contact Load Current Rating: 6.0 amperes resistive load highest ac voltage rating at sea level  Special Features: Black actuator  Style Designator: In-line, cam actuated  Shelf Life: N/a	-
Contact Load Current Rating:  6.0 amperes resistive load highest ac voltage rating at sea level  Special Features:  Black actuator  Style Designator:	Contact Load Current Rating:  6.0 amperes resistive load highest ac voltage rating at sea level  Special Features:  Black actuator  Style Designator:  In-line, cam actuated  Shelf Life:  N/a	-
6.0 amperes resistive load highest ac voltage rating at sea level  Special Features:  Black actuator  Style Designator:	6.0 amperes resistive load highest ac voltage rating at sea level  Special Features:  Black actuator  Style Designator:  In-line, cam actuated  Shelf Life:  N/a	
Black actuator  Style Designator:	Black actuator  Style Designator: In-line, cam actuated  Shelf Life: N/a	6.0 amperes resistive load highest ac voltage rating at sea level
Style Designator:	Style Designator: In-line, cam actuated Shelf Life: N/a	
	In-line, cam actuated  Shelf Life: N/a	Black actuator
	Shelf Life: N/a	Style Designator:
In-line, cam actuated	N/a	In-line, cam actuated
Shelf Life:		Shelf Life:
	Unit Of Measure:	N/a
N/a		Unit Of Measure:
N/a		

--

## NSN 5930-01-052-3432

Rotary Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A052b0