NSN 5930-01-052-3433

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-052-3433

Thread Class:

2a single mounting facility

Thread Length:

0.250 inches single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

0.915 inches

Shaft Diameter:

0.125 inches single actuator

Shaft Length:

0.093 inches single actuator

Overall Diameter:

0.500 inches

Individual Section Quantity:

1

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 single section rear

Throw Quantity:

3 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thready Qty Per Inch (tpi):

24 single mounting facility

Thread Size:

0.216 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round, slotted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks single section rear

Switch Actuator Positioning Increment:

36.0 degrees single actuator

NSN 5930-01-052-3433

Rotary Switch - Page 2 of 2



Switch Actuator Stop Device Type: Fixed stop single actuator

Contact Load Current Rating:

250.0 milliamperes resistive load dc at sea level

Style Designator:

Snap or line

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0