

View Online at <https://aerobasegroup.com/nsn/5930-01-052-3436>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Shock proof and vibration resistant

Body Diameter:

Between 0.485 inches and 0.515 inches

Bushing Length:

1.277 inches

Body Length:

1.098 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.305 inches and 0.315 inches

Actuator Free Position Height:

Between 0.285 inches and 0.315 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Hermetically sealed

Thread Size:

0.500 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

16.0 ounces

Switch Actuating Force:

112.0 ounces

Actuator Movement:

Between 0.020 pretravel inches and 0.250 overtravel inches and 0.010 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

1.500 amperes resistive dc and 750.000 milliamperes inductive dc

Thread Series Designator:

Unef

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0