

View Online at <https://aerobasegroup.com/nsn/5930-01-052-3436>

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Shock proof and vibration resistant

**Body Diameter:**

Between 0.485 inches and 0.515 inches

**Bushing Length:**

1.277 inches

**Body Length:**

1.098 inches

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.305 inches and 0.315 inches

**Actuator Free Position Height:**

Between 0.285 inches and 0.315 inches

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Hermetically sealed

**Thread Size:**

0.500 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

16.0 ounces

**Switch Actuating Force:**

112.0 ounces

**Actuator Movement:**

Between 0.020 pretravel inches and 0.250 overtravel inches and 0.010 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

1.500 amperes resistive dc and 750.000 milliamperes inductive dc

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

3 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0