## NSN 5930-01-052-5027

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-052-5027

Body Style:
Hole mounted
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.880 inches
Body Length:
1.090 inches
Body Width:
0.400 inches
Body Height:
0.630 inches
Unthreaded Mounting Hole Diameter:
0.110 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.410 inches
Actuator Length:
1.340 inches
Actuator Style:
Roller arm
Actuator Free Position Height:
0.810 inches
Actuator Roller Diameter:
0.190 inches
Actuator Roller Width:
0.190 inches
Maximum Voltage Rating In Volts:
250.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
1 pole, double throw, both positions maintained single switch unit
Switch Release Force:
0.500 ounces
Switch Actuating Force:
2.5 ounces
Actuator Movement:
Between 0.125 pretravel inches and 0.085 overtravel inches and 0.030 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
500.000 milliamperes resistive dc and 15.100 amperes resistive ac
Terminal Type And Quantity:
3 quick disconnect, male
Shelf Life:
N/a

## NSN 5930-01-052-5027

Sensitive Switch - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A053a0