

View Online at <https://aerobasegroup.com/nsn/5930-01-052-5027>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.880 inches

Body Length:

1.090 inches

Body Width:

0.400 inches

Body Height:

0.630 inches

Unthreaded Mounting Hole Diameter:

0.110 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.410 inches

Actuator Length:

1.340 inches

Actuator Style:

Roller arm

Actuator Free Position Height:

0.810 inches

Actuator Roller Diameter:

0.190 inches

Actuator Roller Width:

0.190 inches

Maximum Voltage Rating In Volts:

250.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

0.500 ounces

Switch Actuating Force:

2.5 ounces

Actuator Movement:

Between 0.125 pretravel inches and 0.085 overtravel inches and 0.030 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

500.000 milliamperes resistive dc and 15.100 amperes resistive ac

Terminal Type And Quantity:

3 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0