## NSN 5930-01-052-6449

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-052-6449

Overall Length:
0.956 inches
Overall Height:
0.300 inches
Body Diameter:
0.660 centimeters
End Application:
Flir 96214
Tempurature Sensing Element Type:
Internal sensor
Operating Tempurature Rating:
Between -10.0 degrees fahrenheit and 400.0 degrees fahrenheit
Mounting Method:
Clamp
Features Provided:
Hermetically sealed case
Contact Action Stimulus:
Increase
Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

## **Terminal Type:**

Tab, solder lug

Contact Load Current Rating:

2.0 amperes resistive load second voltage and 1.0 amperes inductive load second voltage and 1.0 amperes lamp load second voltage

### **Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

### **Contact Stimulus Rating:**

197.00 actuation point degrees fahrenheit and 192.00 deactuation point degrees fahrenheit and 195.00 deactuation point degrees fahrenheit

### **Contact Voltage Rating In Volts:**

28.0 dc at sea level second voltage

## Frequency In Hertz:

60.0 first voltage

## Media For Which Designed:

Gas or liquid

### Style Designator:

Disc

## Test Data Document:

81349-mil-s-24236 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Specification Data:**

81349-mil-s-24236/20 government specification

## Shelf Life:

NI/o

# NSN 5930-01-052-6449

Thermostatic Switch - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A048b0

