

View Online at <https://aerobasegroup.com/nsn/5930-01-052-6450>

**Hazardous Locations/environmental Protection:**

Vibration resistant

**Overall Length:**

0.834 inches

**Overall Height:**

0.344 inches

**Body Diameter:**

0.660 inches

**Mounting Slot Width:**

0.104 inches

**Distance Between Mounting Facility Centers:**

Between 0.937 inches and 0.999 inches

**Temperature Sensing Element Type:**

Internal sensor

**Operating Temperature Rating:**

Between -65.0 degrees fahrenheit and 500.0 degrees fahrenheit

**Mounting Method:**

Bracket and slot

**Features Provided:**

Hermetically sealed case

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action

**Terminal Type:**

Tab, solder lug

**Contact Load Current Rating:**

5.0 amperes resistive load second voltage and 2.5 amperes inductive load second voltage and 1.0 amperes lamp load second voltage

**Contact Adjustability:**

Actuation point not adjustable and deactuation point not adjustable

**Contact Stimulus Rating:**

0.00 actuation point degrees fahrenheit and -2.00 deactuation point degrees fahrenheit

**Contact Voltage Rating In Volts:**

28.0 dc at sea level second voltage

**Frequency In Hertz:**

60.0 first voltage

**Media For Which Designed:**

Gas

**Precious Material And Location:**

Contacts silver

**Precious Material:**

Silver

**Style Designator:**

Disc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0