## NSN 5930-01-052-7285

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-052-7285

View Online at https://aerobasegroup.com/nsn/5930-01-052-7285
Overall Length:
1.704 inches
Overall Height:
1.068 inches
Body Diameter:
1.234 inches
Body Height:
0.688 inches
Unthreaded Mounting Hole Diameter:
Between 0.094 inches and 0.172 inches
Distance Between Mounting Facility Centers:
1.469 inches
Tempurature Sensing Element Type:
Internal sensor
Mounting Method:
Bracket and unthreaded hole
Features Provided:
Hermetically sealed case
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Tab, solder lug
Contact Load Current Rating:
4.0 amperes resistive load second voltage
Contact Adjustability:
Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable
Deactuation point not adjustable and actuation point not adjustable
Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:
Deactuation point not adjustable and actuation point not adjustable <b>Contact Stimulus Rating:</b> 203.00 actuation point degrees fahrenheit and 167.00 deactuation point degrees fahrenheit
Deactuation point not adjustable and actuation point not adjustable <b>Contact Stimulus Rating:</b> 203.00 actuation point degrees fahrenheit and 167.00 deactuation point degrees fahrenheit <b>Contact Voltage Rating In Volts:</b>
Deactuation point not adjustable and actuation point not adjustable <b>Contact Stimulus Rating:</b> 203.00 actuation point degrees fahrenheit and 167.00 deactuation point degrees fahrenheit <b>Contact Voltage Rating In Volts:</b> 30.0 dc at sea level third voltage
Deactuation point not adjustable and actuation point not adjustable <b>Contact Stimulus Rating:</b> 203.00 actuation point degrees fahrenheit and 167.00 deactuation point degrees fahrenheit <b>Contact Voltage Rating In Volts:</b> 30.0 dc at sea level third voltage <b>Media For Which Designed:</b>
Deactuation point not adjustable and actuation point not adjustable <b>Contact Stimulus Rating:</b> 203.00 actuation point degrees fahrenheit and 167.00 deactuation point degrees fahrenheit <b>Contact Voltage Rating In Volts:</b> 30.0 dc at sea level third voltage <b>Media For Which Designed:</b> Gas or liquid
Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 203.00 actuation point degrees fahrenheit and 167.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 30.0 dc at sea level third voltage Media For Which Designed: Gas or liquid Style Designator:
Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 203.00 actuation point degrees fahrenheit and 167.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 30.0 dc at sea level third voltage Media For Which Designed: Gas or liquid Style Designator: Disc w/flange

--

## NSN 5930-01-052-7285

Thermostatic Switch - Page 2 of 2

Demilitarization:

No

Fiig:

A048b0

