

View Online at <https://aerobasegroup.com/nsn/5930-01-052-7286>

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

8.782 inches

Overall Height:

4.750 inches

Overall Width:

4.750 inches

First Flat Length:

1.125 inches single actuator

Shaft Diameter:

0.375 inches single actuator

Shaft Length:

1.563 inches single actuator

Unthreaded Mounting Hole Diameter:

0.406 inches 1st mounting facility and 0.410 inches 1st mounting facility

Individual Section Quantity:

4

Longest Horizontal Distance Between Mounting Centers:

3.781 inches 1st mounting facility

Longest Vertical Distance Between Mounting Centers:

3.781 inches 1st mounting facility

End Application:

Switchboard ic 76714

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section rear

Throw Quantity:

3 each section front

Mounting Method:

Bracket 2nd mounting facility

Contact Voltage Rating In Volts:

500.0 ac at sea level

Switch Actuator Momentary Position:

Counterclockwise single actuator

Rotor Through Connection Quantity:

1 each section

Mounting Facility Pattern:

Four position rectangular 1st mounting facility

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, v flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

60.0 amperes resistive load ac at sea level

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0