NSN 5930-01-052-7294

Push Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-01-052-7294

Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Explosion proof and humidity resistant
Overall Length:
2.996 inches
Overall Height:
0.810 inches
Overall Width:
0.810 inches
Body Width:
0.810 inches
Body Height:
0.810 inches
Case Material:
Metal
Maximum Voltage Rating In Volts:
28.0 dc
Mounting Surface To Terminal End Distance:
2.996 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Mounting Method: Panel
-
Panel
Panel Nonpile-up Contact Arrangement:
Panel Nonpile-up Contact Arrangement: 3 pole, double throw, both positions maintained single switch unit
Panel Nonpile-up Contact Arrangement: 3 pole, double throw, both positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage:
Panel Nonpile-up Contact Arrangement: 3 pole, double throw, both positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 1.000 amperes resistive dc and 0.500 amperes inductive dc
Panel Nonpile-up Contact Arrangement: 3 pole, double throw, both positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 1.000 amperes resistive dc and 0.500 amperes inductive dc Precious Material And Location:
Panel Nonpile-up Contact Arrangement: 3 pole, double throw, both positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 1.000 amperes resistive dc and 0.500 amperes inductive dc Precious Material And Location: Contacts gold
Panel Nonpile-up Contact Arrangement: 3 pole, double throw, both positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 1.000 amperes resistive dc and 0.500 amperes inductive dc Precious Material And Location: Contacts gold Terminal Type And Quantity:
Panel Nonpile-up Contact Arrangement: 3 pole, double throw, both positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 1.000 amperes resistive dc and 0.500 amperes inductive dc Precious Material And Location: Contacts gold Terminal Type And Quantity: 1 socket, integrated wire termination
Nonpile-up Contact Arrangement: 3 pole, double throw, both positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 1.000 amperes resistive dc and 0.500 amperes inductive dc Precious Material And Location: Contacts gold Terminal Type And Quantity: 1 socket, integrated wire termination Shelf Life:
Panel Nonpile-up Contact Arrangement: 3 pole, double throw, both positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 1.000 amperes resistive dc and 0.500 amperes inductive dc Precious Material And Location: Contacts gold Terminal Type And Quantity: 1 socket, integrated wire termination Shelf Life: N/a
Panel Nonpile-up Contact Arrangement: 3 pole, double throw, both positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 1.000 amperes resistive dc and 0.500 amperes inductive dc Precious Material And Location: Contacts gold Terminal Type And Quantity: 1 socket, integrated wire termination Shelf Life: N/a
Panel Nonpile-up Contact Arrangement: 3 pole, double throw, both positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 1.000 amperes resistive dc and 0.500 amperes inductive dc Precious Material And Location: Contacts gold Terminal Type And Quantity: 1 socket, integrated wire termination Shelf Life: N/a Unit Of Measure:
Panel Nonpile-up Contact Arrangement: 3 pole, double throw, both positions maintained single switch unit Contact Load Current Rating At Maximum Rated Voltage: 1.000 amperes resistive dc and 0.500 amperes inductive dc Precious Material And Location: Contacts gold Terminal Type And Quantity: 1 socket, integrated wire termination Shelf Life: N/a Unit Of Measure: Demilitarization: