

View Online at <https://aerobasegroup.com/nsn/5930-01-052-7683>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Watertight

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.375 inches

Body Length:

0.876 inches

Body Width:

0.346 inches

Body Height:

0.600 inches

Unthreaded Mounting Hole Diameter:

Between 0.087 inches and 0.090 inches

Actuator Style:

Round

Actuator Diameter:

0.078 inches

Actuator Free Position Height:

0.475 inches

Maximum Voltage Rating In Volts:

30.0 dc

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

Between 5.0 ounces and 19.0 ounces

Actuator Movement:

Between 0.050 pretravel inches and 0.003 overtravel inches and 0.004 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 500.000 milliamperes inductive dc

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0