# NSN 5930-01-052-9690

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-052-9690

# Hazardous Locations/environmental Protection:

Moisture resistant and salt spray resistant and vibration resistant

#### **Overall Length:**

1.203 inches

# **Overall Height:**

0.321 inches

#### **Body Diameter:**

0.605 inches

#### Mounting Slot Width:

0.140 inches

**Body Height:** 

0.227 inches

#### **Unthreaded Mounting Hole Diameter:**

0.140 inches

#### **Distance Between Mounting Facility Centers:**

0.937 inches

# Tempurature Sensing Element Type:

Internal sensor

# **Operating Tempurature Rating:**

Between -30.0 degrees fahrenheit and 350.0 degrees fahrenheit

#### Mounting Method:

Bracket and slot and unthreaded hole

### **Features Provided:**

Hermetically sealed case

#### **Contact Action Stimulus:**

Increase

#### Mounting Facility Pattern:

Two position in-line

# Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

#### **Terminal Type:**

Tab, solder lug

#### **Contact Load Current Rating:**

1.0 amperes resistive load third voltage

#### Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

#### **Contact Stimulus Rating:**

125.00 actuation point degrees fahrenheit and 110.00 deactuation point degrees fahrenheit

#### **Contact Voltage Rating In Volts:**

30.0 dc at sea level fourth voltage

#### Media For Which Designed:

Gas or liquid

# NSN 5930-01-052-9690

Thermostatic Switch - Page 2 of 2

Style Designator:

Disc w/flange

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A048b0

