NSN 5930-01-052-9851

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-052-9851

| Body Style: |
|---|
| Bushing mount |
| Hazardous Locations/environmental Protection: |
| Dustproof |
| Bushing Length: |
| 0.468 inches |
| Body Length: |
| 0.562 inches |
| Body Width: |
| 0.750 inches |
| Case Material: |
| Metal |
| Actuator Style: |
| Round, stepped |
| Actuator Diameter: |
| 0.620 inches |
| Actuator Height: |
| 0.320 inches |
| Actuator Position-action Relationship: |
| Up position momentary and down position maintained and center position maintained |
| Maximum Voltage Rating In Volts: |
| 28.0 dc |
| End Application: |
| Ftf15a aircraft 76301 |
| Mounting Surface To Terminal End Distance: |
| 0.701 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Threaded bushing |
| Thready Qty Per Inch (tpi): |
| 32 |
| Thread Size: |
| 0.469 inches |
| Nonpile-up Contact Arrangement: |
| 1 pole, double throw, one position momentary single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 500.000 milliamperes resistive dc |
| Thread Series Designator: |
| Uns |
| Terminal Type And Quantity: |

3 tab, solder lug

NSN 5930-01-052-9851

Toggle Switch - Page 2 of 2



| _ | | | | | |
|----|---|---|----|----|----|
| ٠. | n | _ | I+ | 18 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0