

View Online at <https://aerobasegroup.com/nsn/5930-01-053-1071>

Body Style:

Panel mounted

Body Width:

1.115 inches

Body Height:

1.085 inches

Case Material:

Plastic

Actuator Length:

1.085 inches

Actuator Style:

Rectangular

Actuator Height:

0.225 inches

Actuator Width:

0.875 inches

Actuator Color:

White single actuator and white single actuator

Illuminated Actuator Color:

White single actuator and white single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

Harpoon cap can test 76301

Mounting Surface To Terminal End Distance:

3.319 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Nonpile-up Contact Arrangement:

4 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 1.500 amperes lamp ac

Test Data Document:

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

16 tab, solder lug

Specification Data:

81349-mil-s-22885/15 government specification

Shelf Life:

N/A

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0