

View Online at <https://aerobasegroup.com/nsn/5930-01-053-5862>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Weatherproof

Bushing Length:

0.470 inches

Body Length:

1.660 inches

Body Width:

1.340 inches

Body Height:

1.708 inches

Actuator Style:

Round

Actuator Diameter:

0.420 inches

Actuator Height:

1.140 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Actuator Position-locking Relationship:

Up position no locking action and down position no locking action and center position locked out

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

4 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 7.500 amperes inductive dc and 5.000 amperes lamp dc and 7.500 amperes resistive ac and 7.500 amperes inductive ac and 4.000 amperes lamp ac

Test Data Document:

81349-mil-s-3950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

UNF

Terminal Type And Quantity:

12 socket, integrated wire termination

Specification Data:

96906-ms27789 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0