## NSN 5930-01-053-9880

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-053-9880

Overall Length:
4.875 inches
Overall Width:
2.625 inches
Body Height:
2.500 inches
Unthreaded Mounting Hole Diameter:
0.281 inches
Distance Between Mounting Facility Centers:
2.406 inches
Capillary Tube Length:
128.000 inches
Bulb Length:
6.000 inches
Bulb Diameter:
1.125 inches
Tempurature Sensing Element Type:
Capillary tube
Operating Tempurature Rating:
276.0 degrees fahrenheit
Mounting Method:
Bracket and unthreaded hole
Features Provided:
Electrical access port
Contact Action Stimulus:
Decrease
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 two circuit, double break/double make, one position momentary
Terminal Type:
Screw
Contact Load Current Rating:
9.6 amperes resistive load fifth voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+185.00/+250.00 actuation point degrees fahrenheit and +183.00/+245.00 deactuation point degrees fahrenheit
Contact Adjustment Type:
External deactuation point screw and external actuation point screw
Contact Voltage Rating In Volts:
550.0 dc at sea level eighth voltage

## NSN 5930-01-053-9880

Thermostatic Switch - Page 2 of 2



Frequency In Hertz:
---------------------

60.0 third voltage

Media For Which Designed:

Gas or liquid

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A048b0