

View Online at <https://aerobasegroup.com/nsn/5930-01-054-2053>

Thread Class:

2a single mounting facility

Thread Length:

6.00 millimeters single mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

41.9 millimeters

First Flat Length:

9.9 millimeters single actuator

Flat Height:

2.4 millimeters single actuator

Shaft Diameter:

6.0 millimeters single actuator

Shaft Length:

11.5 millimeters single actuator

Overall Diameter:

20.0 millimeters

Individual Section Quantity:

2

Nonturn Device Type:

Flatted bushing at 3: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 each section front

Throw Quantity:

6 each section rear

Mounting Method:

Threaded bushing w/panel seal single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

90.0 degrees from nonturn device single actuator

Rotor Through Connection Quantity:

2 each section

Switch Actuator Indexing Position Quantity:

6 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

1.0 amperes resistive load dc at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0