

View Online at <https://aerobasegroup.com/nsn/5930-01-054-2053>

**Thread Class:**

2a single mounting facility

**Thread Length:**

6.00 millimeters single mounting facility

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

41.9 millimeters

**First Flat Length:**

9.9 millimeters single actuator

**Flat Height:**

2.4 millimeters single actuator

**Shaft Diameter:**

6.0 millimeters single actuator

**Shaft Length:**

11.5 millimeters single actuator

**Overall Diameter:**

20.0 millimeters

**Individual Section Quantity:**

2

**Nonturn Device Type:**

Flatted bushing at 3: 00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

2 each section front

**Throw Quantity:**

6 each section rear

**Mounting Method:**

Threaded bushing w/panel seal single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Shaft Flat/slot Angular Location:**

90.0 degrees from nonturn device single actuator

**Rotor Through Connection Quantity:**

2 each section

**Switch Actuator Indexing Position Quantity:**

6 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

1.0 amperes resistive load dc at sea level

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0