## NSN 5930-01-054-4237

**Hazardous Locations/environmental Protection:** 

Moisture proof liilength:

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-054-4237

1.203 inches
Overall Height:
0.281 inches
Body Diameter:
0.625 inches
Mounting Slot Width:
0.140 inches
Body Height:
1.203 inches
Unthreaded Mounting Hole Diameter:
0.140 inches
Distance Between Mounting Facility Centers:
0.937 inches
Tempurature Sensing Element Type:
Internal sensor
Mounting Method:
Bracket and slot and unthreaded hole
Features Provided:
Hermetically sealed case
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Tab, solder lug
Contact Load Current Rating:
3.0 amperes resistive load first voltage
Contact Adjustability:
Deactuation point not adjustable and actuation point not adjustable
Contact Stimulus Rating:
684.00 actuation point degrees fahrenheit and 678.00 deactuation point degrees fahrenheit
Contact Voltage Rating In Volts:
30.0 dc at sea level third voltage
Media For Which Designed:
Gas or liquid
Precious Material:
Silver

## NSN 5930-01-054-4237

Thermostatic Switch - Page 2 of 2



Style Designator:
Disc w/flange
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A048b0