

View Online at <https://aerobasegroup.com/nsn/5930-01-055-3963>

Thread Length:

0.650 inches single pressure connection

Overall Length:

2.500 inches

Outside Diameter:

0.250 inches single connection

Body Length:

1.850 inches

Overall Diameter:

0.870 inches

Pressure Switch Type:

Gage

Width Across Flats:

0.750 inches

Mounting Method:

Input port

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Proof Pressure:

300.00 pounds per square inch

Thread Size:

0.250 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Wire lead

Contact Load Current Rating:

5.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+4.00/+22.00 actuation point pounds per square inch gage and +2.00/+20.00 deactuation point pounds per square inch gage

Contact Adjustment Type:

External actuation point lock ring and external deactuation point lock ring

Contact Stimulus Rating:

3.00 differential point pounds per square inch gage

Contact Voltage Rating In Volts:

115.0 ac at sea level single voltage

Pressure Connector Type:

Plain, threaded external single connection

Frequency In Hertz:

60.0 single voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0