

View Online at <https://aerobasegroup.com/nsn/5930-01-055-9259>

**Thread Class:**

2a

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Waterproof

**Body Diameter:**

0.688 inches

**Bushing Length:**

0.420 inches

**Body Length:**

1.990 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.688 inches

**Actuator Height:**

0.500 inches

**Actuator Color:**

Black single actuator

**Illuminated Actuator Color:**

Natural single actuator

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Rfi shielding

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

2.000 amperes resistive dc and 1.500 amperes inductive dc and 1.000 amperes lamp dc and 2.000 amperes resistive ac and 1.500 amperes inductive ac and 1.000 amperes lamp ac

**Precious Material And Location:**

Contact surfaces gold

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

8 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0