NSN 5930-01-056-1423

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-056-1423

Thread Class:
2b all pressure connection
Overall Length:
4.300 inches
Overall Height:
4.300 inches
Overall Width:
4.100 inches
Unthreaded Mounting Hole Diameter:
0.281 inches
Longest Horizontal Distance Between Mounting Centers:
2.370 inches
Longest Vertical Distance Between Mounting Centers:
1.740 inches
Pressure Switch Type:
Gage
Operating Tempurature Rating:
Between -30.0 degrees fahrenheit and 160.0 degrees fahrenheit
Mounting Method:
Bracket and unthreaded hole
Features Provided:
Electrical access port
Thready Qty Per Inch (tpi):
14 all pressure connection
Contact Action Stimulus:
Increase
Proof Pressure:
300.00 pounds per square inch gage
Thread Size:
0.875 inches all pressure connection
Mounting Facility Pattern:
Two position diagonal
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Screw
Contact Load Current Rating:
6.0 amperes resistive load second voltage
Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

8.25 actuation point gallons per minute and 6.75 deactuation point gallons per minute and 1.50 differential point gallons per minute

NSN 5930-01-056-1423

Pressure Switch - Page 2 of 2



Contact Voltage Rating In Volts: 480.0 ac at sea level first voltage Pressure Connector Type: Plain, threaded internal all connections Media For Which Designed: Liquid Style Designator: Cylindrical Thread Series Designator: Unf all pressure connection Shelf Life: N/a Unit Of Measure: --Demilitarization:

No Fiig: A048b0