NSN 5930-01-056-1423

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-056-1423

| Thread Class: |
|---|
| 2b all pressure connection |
| Overall Length: |
| 4.300 inches |
| Overall Height: |
| 4.300 inches |
| Overall Width: |
| 4.100 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.281 inches |
| Longest Horizontal Distance Between Mounting Centers: |
| 2.370 inches |
| Longest Vertical Distance Between Mounting Centers: |
| 1.740 inches |
| Pressure Switch Type: |
| Gage |
| Operating Tempurature Rating: |
| Between -30.0 degrees fahrenheit and 160.0 degrees fahrenheit |
| Mounting Method: |
| Bracket and unthreaded hole |
| Features Provided: |
| Electrical access port |
| Thready Qty Per Inch (tpi): |
| 14 all pressure connection |
| Contact Action Stimulus: |
| Increase |
| Proof Pressure: |
| 300.00 pounds per square inch gage |
| Thread Size: |
| 0.875 inches all pressure connection |
| Mounting Facility Pattern: |
| Two position diagonal |
| Nonpile-up Contact Arrangement: |
| 1 pole, double throw, one position momentary |
| Terminal Type: |
| Screw |
| Contact Load Current Rating: |
| 6.0 amperes resistive load second voltage |
| Contact Adjustability: |

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

8.25 actuation point gallons per minute and 6.75 deactuation point gallons per minute and 1.50 differential point gallons per minute

NSN 5930-01-056-1423

Pressure Switch - Page 2 of 2



Contact Voltage Rating In Volts: 480.0 ac at sea level first voltage Pressure Connector Type: Plain, threaded internal all connections Media For Which Designed: Liquid Style Designator: Cylindrical Thread Series Designator: Unf all pressure connection Shelf Life: N/a Unit Of Measure: --Demilitarization:

No Fiig: A048b0