

View Online at <https://aerobasegroup.com/nsn/5930-01-056-2979>

Overall Length:

4.000 inches

Overall Height:

5.812 inches

Overall Width:

2.125 inches

Unthreaded Mounting Hole Diameter:

0.266 inches

Distance Between Mounting Facility Centers:

2.624 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Increase

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

7.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+2500.00/+5500.00 actuation point pounds per square inch gage and +500.00/+2000.00 deactuation point pounds per square inch gage

Contact Adjustment Type:

Internal deactuation point screw and internal actuation point screw

Contact Stimulus Rating:

100.00 differential point pounds per square inch gage

Contact Voltage Rating In Volts:

125.0 ac at sea level single voltage

Pressure Connector Type:

Plain, threaded internal single connection

Frequency In Hertz:

60.0 single voltage

Thread Series Designator:

Nptf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0