NSN 5930-01-056-4699

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-056-4699

TL		_	Len		
	II Ea	u	Len	uu	۱.

0.750 inches all pressure connection

End Application:

Air route surveillance radar 3, (arsr3)

Pressure Switch Type:

Differential

Operating Tempurature Rating:

180.0 degrees fahrenheit

Mounting Method:

Inlet connection and outlet connection

Thready Qty Per Inch (tpi):

14 all pressure connection

Contact Action Stimulus:

Increase

Thread Size:

0.500 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Quick disconnect, male

Contact Load Current Rating:

10.0 amperes resistive load first voltage

Contact Adjustability:

Actuation point adjustable, preset

Contact Adjustment Range:

+0.12/+8.00 actuation point gallons per minute

Contact Adjustment Type:

Internal actuation point screw

Contact Stimulus Rating:

4.50 actuation point gallons per minute

Contact Voltage Rating In Volts:

250.0 dc at sea level second voltage

Pressure Connector Type:

Plain, threaded internal all connections

Frequency In Hertz:

60.0 first voltage

Thread Series Designator:

Npt all pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5930-01-056-4699

Pressure Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A048b0