## NSN 5930-01-056-4699

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-056-4699

TL			Len	ماديم	
11	II E	au	Lei	uu	ı.

0.750 inches all pressure connection

**End Application:** 

Air route surveillance radar 3, (arsr3)

**Pressure Switch Type:** 

Differential

**Operating Tempurature Rating:** 

180.0 degrees fahrenheit

**Mounting Method:** 

Inlet connection and outlet connection

Thready Qty Per Inch (tpi):

14 all pressure connection

**Contact Action Stimulus:** 

Increase

**Thread Size:** 

0.500 inches single pressure connection

**Nonpile-up Contact Arrangement:** 

1 pole, double throw, one position momentary

**Terminal Type:** 

Quick disconnect, male

**Contact Load Current Rating:** 

10.0 amperes resistive load first voltage

**Contact Adjustability:** 

Actuation point adjustable, preset

**Contact Adjustment Range:** 

+0.12/+8.00 actuation point gallons per minute

**Contact Adjustment Type:** 

Internal actuation point screw

Contact Stimulus Rating:

4.50 actuation point gallons per minute

**Contact Voltage Rating In Volts:** 

250.0 dc at sea level second voltage

**Pressure Connector Type:** 

Plain, threaded internal all connections

Frequency In Hertz:

60.0 first voltage

**Thread Series Designator:** 

Npt all pressure connection

Shelf Life:

N/a

**Unit Of Measure:** 

--

## NSN 5930-01-056-4699

Pressure Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A048b0